

PenMount	6000	6010
Silicon Lab	C8051F321	EFM8UB10F16G-C
Package	QFN 28 pin	
ESD	USB port 2KV	USB port 8KV
F/W	6.0.0 (blue paint)	1.0.0 (white paint) , 1.2.0 (purple paint)
Resolution	2048x2048	1024x1024 for 6010.1.0.0 4096 x 4096 for 6010.1.2.0
Operating Temperature	-40°C to +85°C	
Storage Temperature	-65°C to +150°C	
Driver支援	RS232: DOS, Windows XP/ XPE/ 2003/ 2008/Vista/ 7 /8 /10,	
	WinCE 4.2/ 5.0/6.0/7.0, Linux (Kernel 2.6 and X-Window mode), QNX 6.2/ 6.3/ 6.4/ 6.5	
	USB: Windows XP/ XPE/ 2003/ 2008/ Vista/ 7 /8 /10, WinCE 4.2/ 5.0/ 6.0/7.0	
	Linux OS (Kernel 2.6 and X-Window mode), QNX 6.4.1/ 6.5 (Inbox support) QNX6.2/ 6.3/ 6.4/ 6.5	
電路	6000 IC can be used in 6010 circuit design.	6010 IC must adopt its own circuit design.
Protocol	6000 標準 Protocol	